

View Online at <https://aerobasegroup.com/nsn/5945-01-102-5610>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.406 inches single mounting facility

**Overall Height:**

1.125 inches

**Overall Width:**

0.525 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Contact Surface Treatment:**

Gold

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

**Features Provided:**

Coil voltage suppression and polarized

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

110.0 milliamperes dc single winding

**Time Delay:**

0.012 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

8 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300