## NSN 5945-01-104-7274

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-104-7274

Overall Length:
0.790 inches
Overall Height:
0.487 inches
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Operating Current Rating And Type:
20.0 milliamperes dc single winding
Time Delay:
50.00 seconds adjustable operate time
Operating Voltage Rating And Type At Specificationified Temp:
cherry and a second s
32.0 volts dc 25 degrees celsius single winding
32.0 volts dc 25 degrees celsius single winding
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> <li>Terminals gold</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> <li>Terminals gold</li> <li>Precious Material:</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> <li>Terminals gold</li> <li>Precious Material:</li> <li>Gold</li> </ul>
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity:
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> <li>Terminals gold</li> <li>Precious Material:</li> <li>Gold</li> <li>Terminal Type And Quantity:</li> <li>5 pin all functions</li> </ul>
<ul> <li>32.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>150.0 milliamperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>28.0 dc</li> <li>Precious Material And Location:</li> <li>Terminals gold</li> <li>Precious Material:</li> <li>Gold</li> <li>Terminal Type And Quantity:</li> <li>5 pin all functions</li> <li>Shelf Life:</li> </ul>
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:
32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Precious Material And Location: Terminals gold Precious Material: Gold Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: