# NSN 5945-01-105-8407

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-105-8407

## **Overall Length:**

### 1.180 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

## **Overall Height:**

1.062 inches

## **Overall Width:**

0.400 inches

## **Environmental Protection:**

Hermetic

## **Unthreaded Mounting Hole Diameter:**

0.096 inches single mounting facility

# Winding Quantity:

# Coil Quantity:

1

1

#### Winding Dc Resistance Rating:

540.0 ohms single winding and 770.0 ohms single winding

#### Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Features Provided:

Polarized

#### Mounting Facility Pattern:

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

8 pin all functions

## **Specification Data:**

81349-mil-r-5757/10 government specification

# NSN 5945-01-105-8407

Electromagnetic Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

