## NSN 5945-01-105-8407

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-105-8407

Overall	Length:
---------	---------

1.180 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

0.125 inches single mounting facility

**Overall Height:** 

1.062 inches

**Overall Width:** 

0.400 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.096 inches single mounting facility

Winding Quantity:

1

**Coil Quantity:** 

Winding Dc Resistance Rating:

540.0 ohms single winding and 770.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 unthreaded hole single mounting facility

**Features Provided:** 

Polarized

**Mounting Facility Pattern:** 

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Test Data Document:** 

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 pin all functions

**Specification Data:** 

81349-mil-r-5757/10 government specification

## NSN 5945-01-105-8407

Electromagnetic Relay - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300