## NSN 5945-01-106-1703

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-106-1703

| Overall Length:   |
|---|
| 1.718 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:       |
| 1.396 inches single mounting facility and 1.446 inches single mounting facility |
| Overall Height:   |
| 1.435 inches  |
| Overall Width:  |
| 0.555 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.150 inches single mounting facility   |
| Frequency In Hertz:   |
| 60.0  |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:  |
| 2 unthreaded hole single mounting facility                                      |
| Features Provided:  |
| Polarized   |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:  |
| 2 pole, double throw, one position momentary                                    |
| Time Delay:   |
| 0.015 seconds fixed operate and release time                                    |
| Operating Voltage Rating And Type At Specificationified Temp:                   |
| 115.0 volts ac 25 degrees celsius single winding                                |
| Main Contact Load Current Rating At Maximum Rated Voltage:                      |
| 2.0 amperes ac lamp load and 2.0 amperes dc lamp load                           |
| Main Contact Maximum Voltage Rating In Volts:                                   |
| 115.0 ac and 28.0 dc  |
| Terminal Type And Quantity:   |
| 8 tab, solder lug all functions   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5945-01-106-1703

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300