NSN 5945-01-106-6736

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-106-6736

Overall	Length:
---------	---------

Between 2.780 inches and 2.840 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.365 inches single mounting facility and 2.385 inches single mounting facility

Overall Height:

Between 2.365 inches and 2.385 inches

Overall Width:

Between 1.090 inches and 1.150 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility and 0.202 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

COI

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Coil voltage suppression and polarized

Cubic Measure:

7.789 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action and 1 pole, single throw, normally closed, double break, momentary action

Operating Current Rating And Type:

120.0 milliamperes dc single winding

Time Delay:

0.04 seconds fixed release time

NSN 5945-01-106-6736

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Terminal Type And Quantity:

5 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300