NSN 5945-01-110-3192

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-110-3192

1.937 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.562 inches single mounting facility Overall Height: 1.812 inches Overall Width: 2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a Unit Of Measure:	Overall Length:
1.562 inches single mounting facility Overall Height: 1.812 inches Overall Width: 2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1.937 inches
Overall Height: 1.812 inches Overall Width: 2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Length:
1.812 inches Overall Width: 2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1.562 inches single mounting facility
Overall Width: 2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Overall Height:
2.688 inches Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1.812 inches
Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Overall Width:
O.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	2.688 inches
Winding Quantity: 1 Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Unthreaded Mounting Hole Diameter:
Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	0.187 inches single mounting facility
Coil Quantity: 1 Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Winding Quantity:
Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1
Duty Type: Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Coil Quantity:
Intermittent Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1
Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Duty Type:
2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Intermittent
Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Mounting Facility Type And Quantity:
In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	2 unthreaded hole single mounting facility
Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Mounting Facility Pattern:
1 pole, single throw, normally closed, momentary action Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	In-line single mounting facility
Operating Voltage Rating And Type At Specificationified Temp: 36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Nonpile-up Main Contact Arrangement:
36.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	1 pole, single throw, normally closed, momentary action
Terminal Type And Quantity: 4 screw all functions Shelf Life: N/a	Operating Voltage Rating And Type At Specificationified Temp:
4 screw all functions Shelf Life: N/a	36.0 volts dc 25 degrees celsius single winding
Shelf Life: N/a	Terminal Type And Quantity:
N/a	4 screw all functions
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A03300	A03300