NSN 5945-01-110-8132

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-110-8132

Overall Length:

3.218 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.611 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility

Overall Height:

2.310 inches

Overall Width:

1.827 inches

Unthreaded Mounting Hole Diameter:

0.156 inches single mounting facility

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Winding Dc Resistance Rating:

27.0 ohms all windings

Duty Type:

Intermittent

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Latching contacts

Cubic Measure:

13.581 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

NSN 5945-01-110-8132

Electromagnetic Relay - Page 2 of 2



Operating Current Rating And Type: 325.0 milliamperes ac all windings Time Delay: 0.025 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts ac 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac **Energizing Element Power Rating:** 7.8 volts-amperes **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Terminal Type And Quantity:** 22 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300