# NSN 5945-01-111-4306

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-111-4306

# **Overall Length:**

1.718 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

# **Overall Height:**

1.310 inches

# **Overall Width:**

1.025 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

#### Hermetic

Fragility Factor:

#### Moderately rugged

Winding Quantity:

# 1

**Purpose For Which Designed:** 

General

### **Coil Quantity:**

1

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

2.307 cubic inches

#### **Mounting Facility Pattern:**

Triangle single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# **Operating Current Rating And Type:**

150.0 milliamperes dc single winding

#### Time Delay:

90.00 seconds fixed operate time

### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

# NSN 5945-01-111-4306

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300