

View Online at <https://aerobasegroup.com/nsn/5945-01-112-0190>

**Thread Class:**

2a second mounting facility

**Thread Direction:**

Right-hand second mounting facility

**Thread Length:**

0.171 inches second mounting facility

**Overall Length:**

1.427 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.375 inches second mounting facility

**Overall Height:**

1.397 inches

**Overall Width:**

0.735 inches

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Gold and platinum and silver

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

387.0 ohms single winding and 473.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 threaded stud second mounting facility

**Storage Type:**

General purpose warehouse

**Thread Qty Per Inch (tpi):**

48 second mounting facility

**Thread Size:**

0.099 inches second mounting facility

**Mounting Facility Pattern:**

In-line second mounting facility

**Nonpile-up Main Contact Arrangement:**

6 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

250.0 milliamperes ac resistive load and 250.0 milliamperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Precious Material And Location:**

Contacts gold and contacts silver

**Precious Material:**

Gold and platinum and silver

**Thread Series Designator:**

Unc second mounting facility

**Terminal Type And Quantity:**

22 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300