

View Online at <https://aerobasegroup.com/nsn/5945-01-112-0190>

Thread Class:

2a second mounting facility

Thread Direction:

Right-hand second mounting facility

Thread Length:

0.171 inches second mounting facility

Overall Length:

1.427 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.375 inches second mounting facility

Overall Height:

1.397 inches

Overall Width:

0.735 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Gold and platinum and silver

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

387.0 ohms single winding and 473.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded stud second mounting facility

Storage Type:

General purpose warehouse

Thread Qty Per Inch (tpi):

48 second mounting facility

Thread Size:

0.099 inches second mounting facility

Mounting Facility Pattern:

In-line second mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

250.0 milliamperes ac resistive load and 250.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts gold and contacts silver

Precious Material:

Gold and platinum and silver

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

22 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300