NSN 5945-01-112-7686



Electromagnetic Relay - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5945-01-112-7686	
Overall Length:	
1.491 inches	
Center To Center Distance Between Mounting Facilities Parallel To Width:	
1.200 inches single mounting facility	
Overall Height:	
0.455 inches	
Overall Width:	
1.460 inches	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Unthreaded Mounting Hole Diameter:	
0.121 inches single mounting facility	

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

10.0 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.990 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

4.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

NSN 5945-01-112-7686

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300