NSN 5945-01-113-4770

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-113-4770 **Overall Height:** 0.280 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 390.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility **Features Provided:** Coil voltage suppression and polarized **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Operating Current Rating And Type:** 29.2 milliamperes dc single winding **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Special Features:** Failure rate level 0.1 percent; lead lg 1.500 in. **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

Specification Data:

81349-mil-r-39016/20 government specification

Shelf Life:

N/a

NSN 5945-01-113-4770

Electromagnetic Relay - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A03300