NSN 5945-01-114-2343

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-114-2343

| Thread Class: |
|---|
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 2.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.875 inches single mounting facility |
| Overall Height: |
| 3.625 inches |
| Overall Width: |
| 2.250 inches |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 10.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 600.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 10 screw all functions |
| Shelf Life: |

N/a

NSN 5945-01-114-2343

Electromagnetic Relay - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300