## NSN 5945-01-115-7256

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-115-7256 **Overall Length:** 0.280 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 2.0 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility **Features Provided:** Polarized and coil voltage suppression **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary **Operating Current Rating And Type:** 12.95 milliamperes dc single winding **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: **Special Features:** Failure rate level 0.1 percent **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 

**Specification Data:** 

5 wire lead all functions

81349-mil-r-39016/24 government specification

Shelf Life:

N/a

## NSN 5945-01-115-7256

Electromagnetic Relay - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A03300