NSN 5945-01-116-5472

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-116-5472
Overall Length:
3.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.125 inches single mounting facility
Overall Height:
3.120 inches
Overall Width:
2.780 inches
Case Material:
Aluminum alloy
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.218 inches single mounting facility and 0.229 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Features Provided:
Polarized
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary
Time Delay:
0.025 seconds fixed operate and release time
Nonpile-up Auxiliary Contact Arrangement:
1 pole, double throw, one position momentary
Auxiliary Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
50.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:

115.0 ac

NSN 5945-01-116-5472

Electromagnetic Relay - Page 2 of 2



Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Terminal Type And Quantity:

14 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300