NSN 5945-01-116-6663

Resonant Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-116-6663

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.375 inches single mounting facility and 0.407 inches single mounting facility

Overall Length:

2.680 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility

Overall Height:

1.531 inches

Overall Width:

1.938 inches

Environmental Protection:

Shock resistant and vibration resistant

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

,

Resonant Reed Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Four position rectangular single mounting facility

Resonant Reed Frequency In Hertz:

420.0 single reed

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

NSN 5945-01-116-6663

Resonant Reed Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

4.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

4 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300