

View Online at <https://aerobasegroup.com/nsn/5945-01-117-8178>

Thread Class:

2b single mounting facility

Overall Length:

3.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

Overall Height:

3.250 inches

Overall Width:

1.031 inches

Environmental Protection:

Dust tight and shock resistant and vibration resistant

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

778.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

36c

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Time Delay:

0.03 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contact surfaces and terminal surfaces gold and contacts silver

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

110 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300