NSN 5945-01-117-8178

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-117-8178 **Thread Class:** 2b single mounting facility **Overall Length:** 3.125 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.750 inches single mounting facility **Overall Height:** 3.250 inches **Overall Width:** 1.031 inches **Environmental Protection:** Dust tight and shock resistant and vibration resistant **Contact Material:** Silver **Contact Surface Treatment:** Gold **Winding Quantity: Coil Quantity:** Winding Dc Resistance Rating: 778.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded hole single mounting facility **Pile-up Main Contact Form Arrangement:** 36c Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility Time Delay: 0.03 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-01-117-8178

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contact surfaces and terminal surfaces gold and contacts silver

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

110 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300