# NSN 5945-01-117-9893

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-117-9893

Overall Length:

0.280 inches

**Overall Diameter:** 

0.370 inches

**Environmental Protection:** 

Hermetic

### Winding Quantity:

1

### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

1.56 kilohms single winding

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

1 terminal single mounting facility

### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

### **Criticality Code Justification:**

Feat

### Time Delay:

0.002 seconds fixed operate time

### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

### **Special Features:**

Failure rate level 0.1 percent

### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

8 wire lead all functions

### **Specification Data:**

81349-mil-r-39016/9 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5945-01-117-9893

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300

