# NSN 5945-01-118-1341

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-118-1341

**Overall Length:** 

0.280 inches

**Overall Diameter:** 

0.370 inches

**Environmental Protection:** 

Hermetic

#### Winding Quantity:

1

### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

2.0 kilohms single winding

**Duty Type:** 

Continuous

### Mounting Facility Type And Quantity:

1 terminal single mounting facility

#### **Features Provided:**

Polarized and coil voltage suppression

## Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

# Criticality Code Justification:

Feat

#### Time Delay:

0.004 seconds fixed release time

### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc resistive load

### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

### **Special Features:**

Established reliability; failure rate 0.1

### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

5 wire lead all functions

#### **Specification Data:**

81349-mil-r-39016/24 government specification

Shelf Life:

N/a

- Unit Of Measure:
- ---

# NSN 5945-01-118-1341

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

