# NSN 5945-01-119-0954

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-119-0954

#### **Overall Height:**

0.280 inches

**Overall Diameter:** 

0.370 inches

**Environmental Protection:** 

Hermetic

#### Winding Quantity:

2

#### **Coil Quantity:**

2

#### Winding Dc Resistance Rating:

125.0 ohms all windings

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

1 terminal single mounting facility

#### **Features Provided:**

Coil voltage suppression and latching contacts and polarized

#### Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

# Criticality Code Justification:

Feat

#### Time Delay:

0.0015 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

6.0 volts dc 25 degrees celsius all windings

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

# Main Contact Maximum Voltage Rating In Volts:

28.0 dc

## **Special Features:**

Failure rate level 0.1 percent; lead lg 1.500 in.

## Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

7 wire lead all functions

## **Specification Data:**

81349-mil-r-39016/27 government specification

### Shelf Life:

N/a

- Unit Of Measure:
- --

# NSN 5945-01-119-0954

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

