

View Online at <https://aerobasegroup.com/nsn/5945-01-119-6810>

Thread Class:

2a single mounting facility

Overall Length:

1.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.187 inches single mounting facility

Overall Height:

2.087 inches

Overall Width:

1.531 inches

Environmental Protection:

Hermetic

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Thread Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac resistive load and 20.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

96906-ms27418 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.