# NSN 5945-01-119-8173

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-119-8173

## **Overall Height:**

0.280 inches

**Overall Diameter:** 

0.370 inches

# **Environmental Protection:**

Hermetic

## Winding Quantity:

2

## **Coil Quantity:**

2

## Winding Dc Resistance Rating:

2.0 kilohms all windings

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

1 terminal single mounting facility

#### **Features Provided:**

Coil voltage suppression and latching contacts and polarized

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# **Operating Current Rating And Type:**

13.0 milliamperes dc all windings

## Criticality Code Justification:

Feat

#### Time Delay:

0.002 seconds fixed operate time

## **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius all windings

## Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

# Main Contact Maximum Voltage Rating In Volts:

28.0 dc

# **Special Features:**

Failure rate level 0.1 percent; one coil terminal common to both coils

# Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

9 wire lead all functions

# **Specification Data:**

81349-mil-r-39016/30 government specification

# Shelf Life:

N/a

# NSN 5945-01-119-8173

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

