# NSN 5945-01-120-0313

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-120-0313

#### **Thread Class:**

2a single mounting facility

#### **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

1.500 inches

#### **Overall Diameter:**

0.925 inches

#### Winding Quantity:

1

# Coil Quantity:

1

#### Winding Dc Resistance Rating:

335.0 ohms single winding

Duty Type:

## Continuous

Mounting Facility Type And Quantity:

1 threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.562 inches single mounting facility

#### Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

#### Time Delay:

0.006 seconds fixed operate and release time

## Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes dc resistive load

## Main Contact Maximum Voltage Rating In Volts:

2500.0 dc

# Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Thread Series Designator:

Uns single mounting facility

# Terminal Type And Quantity:

5 tab, solder lug all functions

## **Specification Data:**

81349-mil-r-83725/4 government specification

# Shelf Life:

N/a

# NSN 5945-01-120-0313

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

