## NSN 5945-01-120-1115

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-120-1115  |
|--|
| Overall Length:  |
| 0.375 inches   |
| Overall Diameter:  |
| 0.370 inches   |
| Environmental Protection:  |
| Hermetic   |
| Fragility Factor:  |
| Moderately rugged  |
| Winding Quantity:  |
| 1  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 255.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Mounting Facility Type And Quantity:   |
| 1 terminal single mounting facility  |
| Storage Type:  |
| General purpose warehouse  |
| Nonpile-up Main Contact Arrangement:   |
| 1 pole, double throw, one position momentary   |
| Criticality Code Justification:  |
| Feat   |
| Time Delay:  |
| 0.004 seconds fixed operate time   |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 6.0 volts dc 25 degrees celsius single winding   |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 100.0 milliamperes dc lamp load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 28.0 dc  |
| Special Features:  |
| Failure rate level 0.1 percent; lead lg 1.500 in.  |
| Test Data Document:  |
| 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 5 wire lead all functions  |
| Specification Data:  |

N/a

Shelf Life:

81349-mil-r-39016/10 government specification

## NSN 5945-01-120-1115

Electromagnetic Relay - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A03300