

View Online at <https://aerobasegroup.com/nsn/5945-01-120-3848>

**Overall Length:**

1.415 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.200 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.400 inches single mounting facility

**Overall Height:**

1.020 inches

**Overall Width:**

0.610 inches

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.096 inches single mounting facility

**Contact Material:**

Silver and nickel

**Contact Surface Treatment:**

Gold

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

500.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.006 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

250.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Terminal Type And Quantity:**

14 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300