## NSN 5945-01-120-8421

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-120-8421

**Overall Height:** 0.375 inches **Overall Diameter:** 0.370 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 1.6 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 terminal single mounting facility **Features Provided:** Coil voltage suppression and polarized **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Operating Current Rating And Type:** 10.9 milliamperes dc single winding **Criticality Code Justification:** Feat Time Delay: 0.0075 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 18.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Special Features:** Failure rate level 0.1 percent; 0.500 in. lead lg **Test Data Document:** 81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 

**Specification Data:** 

8 wire lead all functions

81349-mil-r-39016/21 government specification

Shelf Life:

N/a

## NSN 5945-01-120-8421

Electromagnetic Relay - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A03300