## NSN 5945-01-122-3913

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-122-3913
Overall Height:
0.280 inches
Overall Diameter:
0.370 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
98.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Features Provided:
Coil voltage suppression and polarized
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.004 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
28.0 dc
Special Features:
Failure rate level 0.1 percent
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 wire lead all functions
Specification Data:
81349-mil-r-39016/15 government specification
Shelf Life:
N/a

-

**Unit Of Measure:** 

## NSN 5945-01-122-3913

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300