NSN 5945-01-122-9077

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-122-9077 **Overall Length:** 0.500 inches **Overall Diameter:** 0.375 inches **Environmental Protection:** Shock resistant and vibration resistant **Contact Material:** Gold **Contact Surface Treatment:** Gold **End Application:** Forrestal class cv, sturgeon class ssn (637), los angeles class ssn (688), oliver perry class ffg, nimitz class cvn, emory s. Land class as, mercy and comfort hospital ships class tah. General purpose electronic test equipment (gpete). Mx peacekeeper missle support equipment. Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 390.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary **Criticality Code Justification:** Feat Time Delay: 0.004 seconds fixed operate time Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Special Features:** Weapon system essential **Precious Material And Location:**

Contacts and contact surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

10 wire lead all functions

Shelf Life:

N/a

NSN 5945-01-122-9077

Electromagnetic Relay - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A03300