

View Online at <https://aerobasegroup.com/nsn/5945-01-122-9077>

Overall Length:

0.500 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Shock resistant and vibration resistant

Contact Material:

Gold

Contact Surface Treatment:

Gold

End Application:

Forrestal class cv, sturgeon class ssn (637), los angeles class ssn (688), oliver perry class ffg, nimitz class cvn, emory s. Land class as, mercy and comfort hospital ships class tah. General purpose electronic test equipment (gpete). Mx peacekeeper missile support equipment.

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

390.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.004 seconds fixed operate time

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Weapon system essential

Precious Material And Location:

Contacts and contact surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

10 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300