

View Online at <https://aerobasegroup.com/nsn/5945-01-122-9078>

**Overall Length:**

3.660 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.100 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.100 inches single mounting facility

**Overall Height:**

4.440 inches

**Overall Width:**

3.660 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.201 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

12.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action

**Time Delay:**

0.05 seconds fixed release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action and 1 pole, single throw, normally closed, double break, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

230.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

120.0 amperes dc motor load

**Main Contact Maximum Voltage Rating In Volts:**

440.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

**Terminal Type And Quantity:**

12 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300