# NSN 5945-01-123-0591

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-123-0591

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.312 inches single mounting facility
Overall Length:
1.000 inches
Overall Height:
1.762 inches
Overall Width:
0.980 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
0-11 0
Coil Quantity:
Coil Quantity:
1
1 Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 650.0 ohms single winding
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.727 cubic inches
Winding Dc Resistance Rating: 650.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 1.727 cubic inches Thready Qty Per Inch (tpi):

# NSN 5945-01-123-0591

Electromagnetic Relay - Page 2 of 2



#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

Time Delay:

0.013 seconds fixed operate time

## **Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 32.0 dc

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300