

View Online at <https://aerobasegroup.com/nsn/5945-01-123-1430>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.320 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

290.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

2.324 cubic inches

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Time Delay:**

0.015 seconds fixed operate and release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

15.0 amperes ac inductive load and 12.0 amperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes ac lamp load and 500.0 milliamperes dc lamp load

**Terminal Type And Quantity:**

11 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300