

View Online at <https://aerobasegroup.com/nsn/5945-01-123-8508>

Overall Length:

4.235 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.687 inches single mounting facility

Overall Height:

4.351 inches

Overall Width:

4.220 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.220 inches single mounting facility and 0.233 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Coil voltage suppression

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Time Delay:

0.06 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes ac resistive load and 100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Terminal Type And Quantity:

11 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300