## NSN 5945-01-125-0943

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-125-0943

**Overall Length:** 

0.370 inches

**Overall Height:** 

0.275 inches

**Overall Width:** 

0.370 inches

**Environmental Protection:** 

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

39.0 ohms single winding

**Duty Type:** 

Continuous

Mounting Facility Type And Quantity:

1 terminal single mounting facility

**Features Provided:** 

Coil voltage suppression and polarized

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

**Time Delay:** 

0.004 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

5.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

**Special Features:** 

Failure rate level 0.1 percent

## **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

8 wire lead all functions

**Specification Data:** 

81349-mil-r-39016/19 government specification

Shelf Life:

N/a

## NSN 5945-01-125-0943

Electromagnetic Relay - Page 2 of 2



---

Demilitarization:

No

Fiig:

A03300

