

View Online at <https://aerobasegroup.com/nsn/5945-01-126-3691>

Overall Length:

5.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.812 inches single mounting facility

Overall Height:

4.375 inches

Overall Width:

4.620 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

48.5 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

0.025 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

6 pole, single throw, normally open, momentary action and 6 pole, single throw, normally closed, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

18.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

175.0 amperes ac motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc lamp load

Terminal Type And Quantity:

9 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300