

View Online at <https://aerobasegroup.com/nsn/5945-01-126-3691>

**Overall Length:**

5.560 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.812 inches single mounting facility

**Overall Height:**

4.375 inches

**Overall Width:**

4.620 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.218 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

48.5 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Features Provided:**

Polarized

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Time Delay:**

0.025 seconds fixed operate and release time

**Nonpile-up Auxiliary Contact Arrangement:**

6 pole, single throw, normally open, momentary action and 6 pole, single throw, normally closed, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

18.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

175.0 amperes ac motor load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc lamp load

**Terminal Type And Quantity:**

9 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300