

View Online at <https://aerobasegroup.com/nsn/5945-01-126-7921>

Overall Length:

3.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.687 inches single mounting facility

Overall Height:

4.548 inches

Overall Width:

3.305 inches

Case Material:

Metal

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

52.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

750.0 milliamperes dc lamp load

Terminal Type And Quantity:

12 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300