# NSN 5945-01-126-8204

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-126-8204

# **Overall Length:**

3.125 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

## **Overall Height:**

3.250 inches

**Overall Width:** 

1.031 inches

Environmental Protection:

Shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

0.166 inches single mounting facility

## **Contact Material:**

Silver

### **Contact Surface Treatment:**

Gold and rhodium plated

#### Winding Quantity:

1

### Coil Quantity:

1

### Duty Type:

Continuous

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

### Pile-up Main Contact Form Arrangement:

36c

### Mounting Facility Pattern:

Rectangular single mounting facility

### Time Delay:

0.03 seconds fixed operate time

# Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

## Precious Material And Location:

Contact surfaces gold and contacts and terminal surfaces silver and contact surfaces rhodium

## Precious Material:

Gold and silver and rhodium

# NSN 5945-01-126-8204

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:

101 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300