

View Online at <https://aerobasegroup.com/nsn/5945-01-126-8204>

**Overall Length:**

3.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.750 inches single mounting facility

**Overall Height:**

3.250 inches

**Overall Width:**

1.031 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.166 inches single mounting facility

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold and rhodium plated

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Pile-up Main Contact Form Arrangement:**

36c

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Time Delay:**

0.03 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

125.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Precious Material And Location:**

Contact surfaces gold and contacts and terminal surfaces silver and contact surfaces rhodium

**Precious Material:**

Gold and silver and rhodium

**Terminal Type And Quantity:**

101 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300