NSN 5945-01-127-1105

Electromagnetic Relay - Page 1 of 2

2.000 inches single mounting facility

Overall Length: 2.500 inches

Overall Height: 2.340 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-01-127-1105

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.531 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.232 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
2 unthreaded hole single mounting facility Storage Type:
Storage Type:
Storage Type: General purpose warehouse
Storage Type: General purpose warehouse Cubic Measure:
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern:
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement:
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type:
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 60.0 milliamperes dc single winding
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 60.0 milliamperes dc single winding Time Delay:
Storage Type: General purpose warehouse Cubic Measure: 8.956 cubic inches Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 60.0 milliamperes dc single winding Time Delay: 1.50 seconds fixed operate time

NSN 5945-01-127-1105

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300