

View Online at <https://aerobasegroup.com/nsn/5945-01-128-6163>

Overall Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.870 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.870 inches single mounting facility

Overall Height:

4.630 inches

Overall Width:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

225.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

75.0 amperes ac resistive load and 75.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

15000.0 ac and 15000.0 dc

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw contacts

Specification Data:

81349-mil-r-83725/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300