## NSN 5945-01-129-5680

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 0.800 inches



View Online at https://aerobasegroup.com/nsn/5945-01-129-5680

Overall Height:
0.900 inches
Overall Width:
0.400 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
540.0 ohms single winding and 770.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.288 cubic inches

2 pole, double throw, one position momentary

**Nonpile-up Main Contact Arrangement:** 

Time Delay:

0.006 seconds fixed operate and release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes ac lamp load and 100.0 milliamperes dc lamp load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5945-01-129-5680

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:
8 pin all functions
Specification Data:
81349-mil-r-5757/10 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

ı ııg.

A03300