

View Online at <https://aerobasegroup.com/nsn/5945-01-130-1398>

**Overall Length:**

1.390 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.062 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.281 inches single mounting facility

**Overall Height:**

1.110 inches

**Overall Width:**

0.462 inches

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.120 inches single mounting facility

**Winding Quantity:**

2

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

300.0 ohms all windings

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Features Provided:**

Polarized and latching contacts

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.005 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

150.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

10 tab, solder lug all functions

**Specification Data:**

81349-mil-r-39016/32 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300