

View Online at <https://aerobasegroup.com/nsn/5945-01-131-3721>

**Overall Length:**

3.660 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.090 inches single mounting facility and 3.110 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.090 inches single mounting facility and 3.110 inches single mounting facility

**Overall Height:**

4.440 inches

**Overall Width:**

3.660 inches

**Case Material:**

Metal

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.191 inches single mounting facility and 0.211 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Frequency In Hertz:**

Between 47.0 and 63.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

59.476 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Time Delay:**

0.125 seconds fixed release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

120.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes dc resistive load

**Precious Material And Location:**

Terminals silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

6 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300