## NSN 5945-01-131-5677

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-131-5677

| Overall Length: |  |
|-----------------|--|
| 1.415 inches    |  |

## **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.190 inches single mounting facility and 1.210 inches single mounting facility

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.390 inches single mounting facility and 0.410 inches single mounting facility

**Overall Height:** 

0.660 inches

**Overall Width:** 

0.845 inches

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.091 inches single mounting facility and 0.101 inches single mounting facility

**Fragility Factor:** 

Moderately rugged

**Winding Quantity:** 

•

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

105.3 ohms single winding and 128.7 ohms single winding

**Duty Type:** 

Continuous

## **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

0.789 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.008 seconds fixed operate and release time

## Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-131-5677

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc inductive load

## **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

14 wire hook all functions

#### **Specification Data:**

81349-mil-r-39016/39 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300