NSN 5945-01-132-6093

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-132-6093

Overall Length:
1.688 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.375 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
1.234 inches
Overall Width:
0.859 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0 and 400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
330.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
1.789 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Cubic Measure: 1.789 cubic inches
Mounting Facility Pattern:
2 pole, double throw, one position momentary

Time Delay:

0.011 seconds fixed operate time

NSN 5945-01-132-6093

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac inductive load

Main Contact Maximum Voltage Rating In Volts:

230.0 ac and 30.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300