# NSN 5945-01-132-6093

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-132-6093

## **Overall Length:**

1.688 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

#### **Overall Height:**

1.234 inches

#### **Overall Width:**

0.859 inches

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

# Frequency In Hertz:

60.0 and 400.0

# Winding Quantity:

1

## Purpose For Which Designed:

General

### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

330.0 ohms single winding

### Duty Type:

Continuous

### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

### Storage Type:

General purpose warehouse

#### Cubic Measure:

1.789 cubic inches

### Mounting Facility Pattern:

Rectangular single mounting facility

# Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# Time Delay:

0.011 seconds fixed operate time

# NSN 5945-01-132-6093

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac inductive load

Main Contact Maximum Voltage Rating In Volts:

230.0 ac and 30.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300