NSN 5945-01-134-5129

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-134-5129

Thread Class:

2b single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

2.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility

Overall Height:

2.844 inches

Environmental Protection:

Shock resistant and vibration resistant

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

258.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

24 pole, single throw, normally open, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

NSN 5945-01-134-5129

Electromagnetic Relay - Page 2 of 2



_							
ш	roc	\sim	us	ΝЛΞ	stαi	112	

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

50 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300